





技术要求:

1.膜壳最大压力为: 1000PSI(69KG/CM²),

水介质温度: 1℃~49℃;

不可用于腐蚀性液体场合;

2.2芯及2芯以上均用三套鞍座箍带。

注: 括号内尺寸参考尺寸。

Technical requirements:

Shell maximum pressure : 1000PSI,(69KG/CM²)

Water medium temperature: 1 to 49;

Can not be used in corrosive liquid occasions;

Note: dimensions in brackets refer to dimensions.

长度编码 Length Code	L Inch (mm)	S Span (mm)	A Span (mm)	壳体重量 lb (kg)
25/14	19.09 (485)	16.72 (425)	3.94 (100)	7.0 (3.2)
25/21	26.06 (662)	23.72 (602)	3.94 (100)	9.5 (4.3)
25/40-1	45.08 (1145)	42.72 (1085)	7.87 (200)	16.5 (7.5)
25/40-2	85.08 (2161)	82.72 (2101)	7.87 (200)	31.2 (14.2)
25/40-3	125.08 (3177)	122.72 (3117)	7.87 (200)	45.8 (20.8)
25/40-4	165.08 (4193)	162.72 (4133)	7.87 (200)	60.5 (27.5)

8	内六角螺栓Inner hexagonal head bolt	4	M5*1.5,304
7	月牙片Crescent film	4	SA-213,304
6	膜密封圈Film sealing ring	2	EPDM
5	产品序列号标签Product serial number label	1	铜版纸Art paper
4	大密封圈Large sealing ring	2	EPDM
3	膜壳标签Shell label	1	不干胶标签Self-adhesive label
2	承压头Pressure head	2	2205
1	壳体Housing	1	环氧+玻纤Epoxy + glass fiber
序号	名称	数量	材料

SIGNATURE			 河北成达管业有限公司 HE BEI CHENGDA PIPES Co.,LTD		
	NAME	DATE			
DESIGN			比例 SCALE	材料 MATERIAL	型号 TYPE W25E1000
REVIEW			数量 QUANTITY	光洁度 SMOOTH	描述 DESCRIPTION MEMBRANE HOUSING
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			投影 PROJ	电脑编号 NO.	图号 DRAWING NO. CD-Z-15
			DO NOT MEASURE THE DIMENSIONS.		
			单位UNIT:MM		